

## Ultra Wide Band Coaxial Circulator 100-200MHz



Note: Photo is for illustration purposes only.  
Please refer to outline drawing.

### Product Description

RFLC101M10M20 is an ultra wide band coaxial circulator with a frequency range of 100 to 200MHz.

The circulator has a typical isolation of 15dB. The maximum insertion loss is 1.43dB.

The operating temperature of this product is within -20 to +75°C

### Features

- High power handling up to 50W
- High isolation within operational band
- Low Insertion Loss
- Stable performance over temperature

### Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations


### Electrical Specifications( $T_A=25^\circ\text{C}$ )

Parameter	Min	Typ	Max	Units
Frequency Range		100 – 200		MHz
Insertion Loss		1.45	1.5	dB
Isolation	14	15		dB
VSWR		1.4	1.43	:1
Forward Power (CW)			50	W
Reverse Power (CW)			10	W
Rotation		Clockwise (Standard) Counter Clockwise (Upon Request)		
Input / Output Connectors		RFLC101M10M20S (SMA-Female) RFLC101M10M20N (N-Female)		
Impedance		50		$\Omega$

**Environmental Specifications and Test Standards**


Parameter	Description
Operational Temperature	-20°C to +75°C (Case Temperature)
Storage Temperature	-40°C to +85°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

**Typical Performance Plots**



Mkr	Trace	X-Axis	Value	Notes
1 ▾	S11	150.0000 MHz	-20.88 dB	
2 ▾	S12	150.0000 MHz	-20.91 dB	
3 ▾	S21	150.0000 MHz	-1.23 dB	
4 ▾	S22	150.0000 MHz	-19.35 dB	
5 ▾	S33	150.0000 MHz	-20.93 dB	

**Outline Drawing**



Additional Information

Documentation	Webpage
ESD Policy	<a href="https://rflambda.com/pdf/rflambda_esd_control.pdf">https://rflambda.com/pdf/rflambda_esd_control.pdf</a>
Connector Torque Specifications	<a href="https://www.rflambda.com/pdf/Torque_Specifications.pdf">https://www.rflambda.com/pdf/Torque_Specifications.pdf</a>
Random Vibration Test Standard	<a href="https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf">https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf</a>

**Ordering Information**

Part Number	Modification	Description
RFLC101M10M20S	SMA–Female Connectors	100MHz-200MHz Coaxial Circulator
RFLC101M10M20N	N–Female Connectors	100MHz-200MHz Coaxial Circulator

**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.