



WIDE BAND 500W HIGH POWER DIRECTIONAL COUPLER 1-2GHz



- Ultra wide band performance 1-2GHz
- High power operation up to 500W CW, 5KW peak power
- Compact size and low loss.
- Low passive inter-modulation product.
- Customized unit available.
- Applicable for base station, repeaters of CMDA GSM and UMTS cellular network

WIDE BAND 500W DIRECTIONAL COUPLER 1-2GHz

Electrical Specifications			
PN (20dB)	RFDC1G2G20	PN (30dB)	RFDC1G2G30
Frequency	1-2GHz	Power	500W CW / 5KW Peak
Coupling	20dB, +/-0.8dB	Insertion Loss	0.20dB
Directivity	22dB (Coupling 20dB) 20dB (Coupling 30dB)	VSWR	1.2:1
Environmental Specifications			
Operational Temp.	-40°C to 85°C base plate	Storage Temp.	-55°C to 120°C base plate
Altitude	45,000 ft		
Mechanical Specifications			
Humidity	95% relative humidity, 65°C 96Hour	Mechanical shock	30G, 11mSec half sin wave, 3 axis both directions
Vibration:	14.2g RMS (15-2000Hz) functional	Connectors:	N-Female Brass, Nickel Plate
	16.2g RMS (15-2000Hz) endurance, 1 hour/axis		Beryllium Copper, Gold Plate PIN






RF-LAMBDA

The power beyond expectations

RFDC1G2GXX

WIDE BAND 500W DIRECTIONAL COUPLER 1-2GHz



Part Number: RFDC1G2GXX

Coupling ratio ---XX
Sample: RFDC1G2G30 (30dB)



DRAWING:

