




### ULTRA WIDE BAND 50W DIRECTIONAL COUPLER 0.5GHZ-2.5GHZ




- Ultra wide band performance 0.5G-2.5GHz
- power operation up to 50W CW
- Compact size and low loss.
- Low passive inter-modulation product.
- Customized unit available.
- Applicable for base station, repeaters of CMDA cellular network


Electrical Specifications			
Frequency	0.5G-2.5GHz	Power	50W CW
Frequency Sensitivity	± 0.7dB	Insertion Loss / VSWR	0.4dB / 1.2 : 1
Directivity	20dB	Coupling	20 ± 1.0dB
Environmental Specifications			
Oper.Temp.	-55°C to 85°C base plate	Storage Temp.	-55°C to 100°C base plate
Altitude	45,000 ft		
Mechanical Specifications			
Humidity	95% relative humidity, 65°C 96Hour	Mechanical shock	30G, 11mSec half sin wave, 3 axis both directions
Vibration:	14.2.5G RMS (15-2000Hz) functional	Connectors:	SMA-Female Brass, Nickel Plate
	16.2.5G RMS (15-2000Hz) endurance, 1 hour/axis		Beryllium Copper, Gold Plate PIN



ULTRA WIDE BAND 50W DIRECTIONAL COUPLER 0.5GHZ-2.5GHZ



### DRAWING:



ULTRA WIDE BAND 50W DIRECTIONAL COUPLER 0.5GHZ-2.5GHZ