



### SPDT Absorptive Electro-Mechanical Switch DC-40GHz



#### Features

- SPDT configuration TTL Control
- Magnetic latching
- Operating life of 1 million cycles
- Guaranteed repeatability of 0.05dB up to 1 million cycles
- Excellent isolation, typically >80 dB to 20GHz
- Terminated ports
- TTL/5V CMOS compatible (optional)

#### Description

RF-Lambda's multiport switch offers low insertion loss and high isolation, which is necessary for high performance test systems. The repeatability and reliability of this switch is vital to ATS measurement accuracy and can cut the cost of ownership by reducing calibration cycles.

Our electro-mechanical switches are made through RF-Lambda's rigorous design and tight manufacturing specifications.

Part Number	description	Typ	Low Freq (GHz)	High Freq (GHz)	Max Power Input(Watts)
RFSPDT40EMC-T	Absorptive Electromechanical Switches	SPDT	DC	40	1
Insert. Loss (dB)	VSWR (Max:1)	Isolation (dB)	Actuator Type	Switching Speed (ms Max)	Contact
0.4(DC~12.4GHz) 0.8(12.4~26.5GHz) 1.0(26.5~40GHz)	1.3(DC~12.4GHz) 1.5(12.4~26.5GHz) 1.8(26.5~40GHz)	80(DC~12.4GHz) 70(12.4~26.5GHz) 70(26.5~40GHz)	Latching Holding reflection	20	Break Before Make
Repeatability (dB) max.	Life Cycle	Connector	Biasing (VDC)	Current (mAdc)	Control
0.05	1,000,000	2.92mm (Female)	+24V (22-28V)	240mA dc (200-300mA dc)	-T for TTL type




### Environmental Specification


Operating temperature:	-20 to 70 ° C
Storage temperature:	-55 to 85 ° C
Thermal Shock:	-20 to 70 ° C (1.5 hours holding, 10 times.)
Sine Vibration:	25 grams rms
Life Cycles:	1,000,000 times
Vibration:	20 grams rms.
Moisture resistance:	65 ° C, 95% RH, 10 days per MIL-STD-202F, Method 106E
Altitude storage:	30,000 feet (per MIL-STD-202F, Method 105C, Condition B)
RFI:	Per MIL-STD-461C, RE02, Part 4
Magnetic field:	<5 gauss 1/4 inch from surface
Hot switching:	2W CW 100W peak, 10us max pulse width

### Typical Performance Plots


Insertion Loss




Input VSWR



Output VSWR





Isolation






**Functional Diagram:**



**Pin Descriptions:**



PIN 1 connect the ground, PIN 2 connect +24V, PIN3 and PIN4 are control PINS.

	PIN1	PIN2	PIN3	PIN4
Position A	GND	+24V	Open	TTL
Position B	GND	+24V	TTL	Open


**Notes:**

- When the power path of the switch is in the off state, the switch port is connected to the load sheet, so at this time the max input power of the port is 1W(CW).
- The negative pole must always be connected to ground. if the negative pole is not connected to power supply ground, catastrophic failure will occur.
- Before switching, microwave signal sources must be cut off.



**Outline Drawing:**

All Dimensions in mm [inches]



**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.