




HIGH POWER FIXED TERMINATION --- RFST100GXX



1.0	Mechanical Specifications	
1.1	Coaxial	N or 7/16 (Male or Female)
1.2	Size	132 X 76 X 76mm 5.19" X 2.99" X 2.99"
1.3	Weight	1.45kg
1.4	External Finish	Body painted with black epoxy enamel

3.0 Electrical Specifications				
PN	Frequency (GHz)	VSWR (max.)	Power (CW)	Peak Power (KW)
RFST100G03	DC-3GHz	1.10	100	5KW
RFST100G06	DC-6GHz	1.20	100	5KW
RFST100G08	DC-8GHz	1.25	100	5KW
RFST100G10	DC-10GHz	1.35	100	5KW
RFST100G18	DC-18GHz	1.55	100	5KW

2.0 Environment specifications		
2.1	Operation Temp.	-40°C~+85°C
2.2	Storage Temp.	-55°C~+125°C
2.3	Altitude	41000 ft
2.4	Vibration	10g rms (15 degree 2KHz)
2.5	Humidity	100% RH at 35c, 95%RH at 40 deg c
2.6	Shock	20G for 11msec
2.7	Cooling	FAN required for long time operation

PAGE 1 OF 1		DATE	Sep 2 nd 1006
<small>PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY</small>		DESIGN	RFPC
		RF-LAMBDA	RFPC
 RFST100GXX HIGH POWER TERMINATION		CAD MODEL REVISION	10
		ASSEMBLY REVISION	VS52
		ASSEMBLY NAME	RFLVR07
www.rflambda.com		DRAWING NUMBER	005-A
RF-LAMBDA		SIZE	IT
		SHEETS	1 OF 1