



### Ultra Wide Band Low Noise Amplifier 0.1GHz~6GHz



#### Feature

- Gain: 30dB Typical
- Noise Figure: 3.0dB Typical
- P1dB Output Power: +24dB m full band
- Supply Voltage: +12V @ 290mA
- 50 Ohm Matched Input / Output
- Size: 3.55" x 1.97" x 1.06"

#### Typical Applications

- Wireless Infrastructure
- RF Microwave & VSAT
- Military & Aerospace
- Test Instrument
- Fiber Optics

Ultra Wide Band Low Noise Amplifier 0.1GHz~6GHz

Electrical Specifications, TA = +25 ° C, With VCC=+12V, 50 Ohm System

Parameter	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	0.1		3	3		6	GHz
Gain	27	30		29	31		dB
Gain Flatness		±2			±1.5		dB
Gain Variation Over Temperature(-45 ~ +85)		±0.8			±0.8		dB
Noise Figure		3.5	6.0		3.0	4.5	dB
Input Return Loss		10			12		dB
Output Return Loss		10			10		dB
Output Power for 1 dB Compression (P1dB)	24	25		24	25		dBm
Saturated Output Power (Psat)		27			26		dBm
Output Third Order Intercept (IP3)		34			33		dBm
Supply Current (Idd) (Vd=+12V)		290	350		290	350	mA
Isolation S12	55	50		50	50		dB
Input Max Power(no damage)			+2			+2	dBm
Weight	100						g
Impedance	50						Ohms
Input /Output Connector	SMA-Female						
Finishing	Standard: Gold 40 micron; Nickel 220 micron thickness						
	Option: Gold 80 micron; Nickel 180 micron thickness						
Material	Aluminum/copper						
Package Sealing	Epoxy Sealing (Standard)						
	Hermetically Seal (Option with extra charge)						



# RF-LAMBDA

The power beyond expectations

## RLNA01M06GB

### Absolute Maximum Ratings

Operating Voltage	+15V
RF Input Power	+2dB m
Operating Temperature(C°)	-45 to +85
Storage Temperature(C°)	-50 to +125

### Biasing Up Procedure


Step 1	Connect Ground Pin
Step 2	Connect input and output
Step 3	Connect +12V biasing
Power OFF Procedure	
Step 1	Turn off +12V biasing
Step 2	Remove RF connection
Step 3	Remove Ground.

### Environment specifications


Operational Temperature (C°)	-45 to+85
Storage Temperature (C°)	-50 to +125
Altitude	30,000 ft. (Epoxy Seal Controlled environment) 60,000 ft 1.0psi min (Hermetically Seal Un-controlled environment) ( Optional )
Vibration	25g rms (15 degree 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40°c
Shock	20G for 11msc half sin wave,3 axis both directions

### Typical performance plots


#### Gain




#### Input VSWR



#### Output VSWR



#### Isolation



Ultra Wide Band Low Noise Amplifier 0.1GHz~6GHz




# RF-LAMBDA


The power beyond expectations

## RLNA01M06GB


### Gain vs. output power




### P1dB vs. Frequency




### Output Third Order Intercept (IP3)




### Noise Figure




### 2nd Harmonic Wave output Power



### 3rd Harmonic Wave output Power



### 4th Harmonic Wave output Power



Ultra Wide Band Low Noise Amplifier 0.1GHz~6GHz



# RF-LAMBDA


The power beyond expectations

## RLNA01M06GB

### Outline Drawing:

All Dimensions in mm (inches)

Heat Sink required during operation



### Ordering Information

Part No	ECCN	Description
RLNAoMo6GB	EAR99	0.1-6GHz LNA Amplifier

### Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Ultra Wide Band Low Noise Amplifier 0.1GHz~6GHz