




### Reflective 2-4GHz Coaxial SP3T Switch



#### Features

- Wide Band Operation 2-4GHz
- TTL compatible driver include
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Temperature Range -45°C~+85°C
- Customization available upon request
- Hermetically sealed package up to 60,000ft available upon request.

Electrical Specifications, TA = +25° C, With Vdd = +28V, & VCTL = 0/ +5V

Description	PN: RFSP3TR0204GH			
	SP3T Reflective Switch			
	Low Power Cold Switching			
Parameters	Min	Typ.	Max	Units
Frequency Range	2~4			GHz
Insertion Loss		2.3	2.5	dB
Insertion Loss Temperature Coefficient		0.01		dB/°C
Isolation	50	55		dB
Input VSWR		1.8	2	ratio
Output VSWR (ON State)		1.8	2	ratio
Output VSWR (OFF State)	15			ratio
Power Dissipation (CW)		22		W
1dB Compression P1dB		46		dBm
IM3		55		dBc
Switching Speed			1	us
Weight	2.3			ounces
Impedance	50			Ω
Biasing(+28V)	120			mA
Input /Output Connector	SMA-Female/SMA-Female (Standard)			
Finishing	Gold Plating			
Material	Aluminum			
Seal	Hermetically Sealed ( optional )			

Reflective Coaxial Single Pole Three Throw Switch 2-4GHz



### Absolute Maximum Ratings

Biassing	+28V
TTL Control Voltage	0~0.8V/2~5V
RF Input power	+47dBm
Operating Temperature(°C)	-45 ~ +85
Storage Temperature(°C)	-50 ~ +125

### Ordering Information


Part No	ECCN	Description
RFSP3TR0204GH	EAR99	SP3T 2-4GHz PIN Diode Switch

### Environment specifications


Operational Temperature (°C)	-45 ~ +85
Storage Temperature (°C)	-50 ~ +125
Altitude	30,000 ft. (Epoxy Seal Controlled environment) 60,000 ft 1.0psi min (Hermetically Seal Un-controlled environment) ( Optional )
Vibration	25g rms (15 degree 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40°C
Shock	20G for 11msc half sin wave, 3 axis both directions

### Typical performance plots


#### Insertion Loss




#### Input VSWR



#### Output VSWR




#### Isolation






### Switching Speed




### Switching Speed





### Outline Drawing:

All Dimensions in mm (inches)



Reflective Coaxial Single Pole Three Throw Switch 2-4GHz

### Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.