Voltage Control Phase Shifter
70MHz-100MHz

Product Description

RVPT0117MBC is a voltage control phase shifter with a frequency range of 70 to 100MHz.

The phase shifter's adjustment range is 360 degrees with phase flatness of ±45deg .The insertion loss is 3.5dB with a typical VSWR of 1.5:1.

Phase shifters are devices used to adjust transmission phase in a system. RF-Lambda phase shifters provide low insertion loss, and equal amplitude (or loss) in all phase states.

The working temperature of this product is between - 40℃ and + 85℃.

Features

- Wide Band Operation 70-100MHz
- 360° Phase Shift
- Low Insertion Loss and Phase Error
- Singe Control Operation

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25ºC)

Parameter	Min	Typ	Max	Units
Frequency Range		70~100		MHz
Phase Range	300	360		deg
Phase Flatness		±45		deg
Insertion Loss		3.5	5.0	dB
Insertion Loss Temperature Coefficient		0.01		dB/ °C
Input VSWR		1.5	2.0	:1
Output VSWR		1.5	2.0	:1
0.1dB Compression Point (P0.1dB)		23		dBm
IIP3		30		dBm
Control Voltage	0	10		V
Current		5 Max.		mA
Impedance		50		Ω
Weight		0.13 Max.		lbs.
Impedance		50		Ohms
Input / Output Connectors		SMA-Female (Input) – SMA-Female (Output)		
Package		Epoxy Sealed (Standard)		
		Hermetically Sealed (Optional)		

RF-LAMBDA USA LLC: www.rflambda.com
Sales: sales@rflambda.com Technical: support@rflambda.com

Absolute Maximum Ratings

Parameter	Rating
Control Voltage	0~15V
RF Input power	+30dBm

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-40ºC to +85ºC (Case Temperature)
Storage Temperature	-50ºC to +105ºC
Thermal Shock	-40ºC → +85ºC (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85ºC for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

**For vibration testing details please see additional information section.

RF-LAMBDA USA LLC: www.rflambda.com
Sales: sales@rflambda.com Technical: support@rflambda.com

Typical Performance Plots

Insertion Loss@+25℃



Input VSWR@+25℃



Output VSWR@+25℃



Insertion Loss@-40℃



Input VSWR@-40℃



Output VSWR@-40℃



Typical Performance Plots

Insertion Loss@+85℃



Input VSWR@+85℃



Output VSWR@+85℃



Insertion Loss vs. Frequency



Input VSWR vs. Voltage(S11)



Output VSWR vs. Voltage(S22)



Typical Performance Plots

Normalized Attenuation vs. Frequency



Phase Shift vs. Frequency



Phase Shift vs. Voltage



IIP3



Outline Drawing



Notes:
1. Package Material: Aluminum
2. Finish: Nickel Plated
3. All dimensions are in millimeters [inches].
4. Housing Tolerances ±0.1 [0.004] unless otherwise specified.
5. Standard torque wrench must be used to secure RF connectors.

Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RVPT0117MBC	Standard	70MHz-100MHz Voltage Control Phase Shifter

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.
RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

RF-LAMBDA USA LLC: www.rflambda.com
Sales: sales@rflambda.com Technical: support@rflambda.com