

## 3-40dB 10W Fixed Attenuator DC - 67 GHz



Note: Photo is for illustration purposes only.  
Please refer to outline drawing.

### Features

- Frequency up to 67GHz
- Broad bandwidth
- Low VSWR
- High Attenuation Precision

### Product Description

RFS1G67VB is a fixed attenuator with a frequency range of DC to 67GHz.

The power handling is 10W average. The max VSWR of 1.6:1.

The working temperature of this product is between - 55°C and + 100°C.

### Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

### Electrical Specifications (T<sub>A</sub>=+25°C)


Parameter	Min	Typ	Max	Units
Frequency Range	DC		67	GHz
Attenuation precision	@3dB-10dB	-1.8/+2.0		dB
	@20dB-40dB	-1.5/+1.8		dB
Attenuation		3-40		dB
VSWR			1.6	: 1
Average Power (CW)		10		W
Peak Power (CW)		50 (5% Duty Cycle, 5 μs Pulse Width)		W
Weight		0.12 Max.		lbs.
Input / Output Connectors	1.85mm-Female(Input)-1.85mm-Male(Output)			

**Environmental Specifications and Test Standards**

Parameter	Description
Operational Temperature	-55°C to +100°C (Case Temperature)
Storage Temperature	-55°C to +125°C
Thermal Shock	-55°C → +100°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

\*\*For vibration testing details please see additional information section.

**Outline Drawing**



**Additional Information**

Documentation	Webpage
ESD Policy	<a href="https://rflambda.com/pdf/rflambda_esd_control.pdf">https://rflambda.com/pdf/rflambda_esd_control.pdf</a>
Connector Torque Specifications	<a href="https://www.rflambda.com/pdf/Torque_Specifications.pdf">https://www.rflambda.com/pdf/Torque_Specifications.pdf</a>
Random Vibration Test Standard	<a href="https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf">https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf</a>

**Ordering Information**

Part Number	Modification	Description
RFS1G67VB	Input connector 1.85mm-Female and Output connector 1.85mm-Male	DC-67GHz Fixed Attenuator

**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.