


## 2KW Water Cooling High Power Circulator 50MHz – 150MHz (5% BW)



Note: Photo is for illustration purposes only.  
Please refer to the outline drawing.

### Product Description

RFC2101-2000W is a 2kw water cooled high power circulator. It is a narrowband product that can support a 5% BW within 50 -150MHz. Each design needs to be tuned to a specific center frequency.

The circulator has a typical isolation of 20dB. The maximum insertion loss is 0.5dB.

The operating temperature of this product is within -40 to +85°C

### Features

- High power handling up to 2KW
- Wide band operation
- High isolation within operational band
- Low Insertion Loss
- Stable performance over temperature

### Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations


### Electrical Specifications(T<sub>A</sub>=25°C)

Parameter	Min	Typ	Max	Units
Frequency Range	50 -150 (5% BW) (108MHz+/- 2.7MHz Shown)			MHz
Insertion Loss			0.50	dB
Isolation (Note 1)	20			dB
VSWR			1.20	:1
Power Handling (CW)			2	KW
Rotation		Clockwise		
Input / Output Connectors		7/16-Female		
Impedance		50		Ω

**Environmental Specifications and Test Standards**


Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +125°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

**Typical Performance Plots**



Mkr	Trace	X-Axis	Value	Notes
1 ▾	S11	108.0000 MHz	-31.28 dB	
2 ▾	S12	108.0000 MHz	-33.76 dB	
3 ▾	S21	108.0000 MHz	-0.22 dB	
4 ▾	S22	108.0000 MHz	-33.15 dB	
5 ▾	S33	108.0000 MHz	-32.65 dB	

Typical Performance Plots



Notes:

1. Package Material: Aluminum Alloy
2. Finish : Nickel
3. All dimensions are in millimeters [inches]
4. Tolerance  $\pm 0.25(0.01)$ , unless otherwise specified.

Additional Information

Documentation	Webpage
Connector Torque Specifications	<a href="https://www.rflambda.com/pdf/Torque_Specifications.pdf">https://www.rflambda.com/pdf/Torque_Specifications.pdf</a>
Random Vibration Test Standard	<a href="https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf">https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf</a>

**Ordering Information**

Part Number	Modification	Description
RFC2101-2000W	Connectors 7/16-Female	50MHz – 150MHz High Power Circulator

**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.