



Ultra Wide Band Coaxial Circulator 190 – 230MHz

Features

- High power handling capability up to 50W
- Wide band operation
- High isolation within operational band
- Low Insertion loss
- Stable performance over temperature
- High peak to average handling capability
- All specifications can be modified upon request

Typical Applications

- Aerospace and military applications
- LMDS multi-carrier operation



Electrical Specifications, T_A=25 °C

Parameter	Min.	Typ.	Max.	Units
Frequency Range	190~230			MHz
Insertion Loss			0.5	dB
Isolation	20			dB
VSWR			1.25	:1
Forward Power (CW)			50	W
Rotation	Clockwise (Standard)			
Input /Output Connectors	SMA-Female			
Finishing	Nickel Plated			
Case Material	Aluminum alloy			
Weight				ounces
Impedance	50			Ω

Note 1: Units which have a narrower frequency bandwidth can achieve higher isolation & lower insertion loss
 Bandwidth (5 ~10) % x Center Frequency (Isolation >25dB)
 Bandwidth (20~30) % x Center Frequency (Isolation >23dB)
 Bandwidth (40~60) % x Center Frequency (Isolation >20dB)
 Ask manufacturer for detail

Ultra Wide Band Coaxial Circulator 190-230MHz




Environmental Specifications


Operational Temperature (°C)	-20 ~ +70
Storage Temperature (°C)	-40 ~ +85
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	10g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35c, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions

Typica Performance Plots


Insertion Loss




Isolation



VSWR 1




VSWR2





Outline Drawing:

All Dimensions in mm [inches]



Ultra Wide Band Coaxial Circulator 190-230MHZ

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.