

## Coaxial Circulator 75MHz - 90MHz



Note: Photo is for illustration purposes only.  
Please refer to the outline drawing

### Product Description

RFLCHXD85M is a coaxial circulator with a frequency range of 75 to 90MHz.

The circulator has a minimum isolation of 20dB. The maximum insertion loss is 0.9dB.

The operating temperature of this product is within -20 °C to +70°C

### Features

- High power handling up to 100W
- Wide band operation
- High isolation within operational band
- Low Insertion Loss
- Stable performance over temperature

### Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations


### Electrical Specifications( $T_A=25^\circ\text{C}$ )

Parameter	Min	Typ	Max	Units
Frequency Range		75 - 90		MHz
Insertion Loss		0.8	0.9	dB
Isolation	20	21		dB
VSWR		1.2	1.25	:1
Forward Power			100	W
Rotation		Clockwise (Standard) Counter Clockwise (Upon Request)		
Input / Output Connectors		N-Female		
Impedance		50		$\Omega$

**Environmental Specifications and Test Standards**


Parameter	Description
Operational Temperature	-20°C to +70°C (Case Temperature)
Storage Temperature	-40°C to +85°C
Thermal Shock	-20°C → +70°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

Typical Performance Plots




Mkr	Trace	X-Axis	Value	Notes
1 ▾	S11	82.5000 MHz	-23.58 dB	
2 ▾	S12	82.5000 MHz	-22.55 dB	
3 ▾	S21	82.5000 MHz	-0.70 dB	
4 ▾	S22	82.5000 MHz	-23.98 dB	
5 ▾	S33	82.5000 MHz	-23.43 dB	

Outline Drawing



Notes:

1. Package Material: Aluminum / Copper
2. Finish: Nickel Plated
3. All dimensions are in millimeters [inches].
4. Standard torque wrench must be used to secure RF connectors.



Additional Information

Documentation	Webpage
ESD Policy	<a href="https://rflambda.com/pdf/rflambda_esd_control.pdf">https://rflambda.com/pdf/rflambda_esd_control.pdf</a>
Connector Torque Specifications	<a href="https://www.rflambda.com/pdf/Torque_Specifications.pdf">https://www.rflambda.com/pdf/Torque_Specifications.pdf</a>
Random Vibration Test Standard	<a href="https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf">https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf</a>

**Ordering Information**

Part Number	Modification	Description
RFLCHXD85M	Connectors N-Female	75MHz-90MHz Coaxial Circulator

**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.