



Coaxial Cavity Band Pass Filter 1.71 - 1.73GHz



Features

- High Rejection
- Low Insertion Loss
- Excellent Temperature Stability
- Miniaturization
- Filter Type: Cavity
- Customization available upon request



Electrical Specifications, $T_A = +25^\circ \text{C}$

Parameters		Min.	Typ.	Max.	Units
Center Frequency			1720		MHz
Band width		20			MHz
Insertion Loss			0.7	1.0	dB
Pass Band Ripple			0.3	0.5	dB
VSWR			1.2	1.25	:1
Rejection	@± 60MHz off center	50	55		dB
Power Rating	Average			30	W
	Peak			0.3	KW
Impedance		50			Ohms
Weight		6.35			Ounces
Input / Output Connectors		N-Female			
Material		Aluminum			
Finishing		Blue Paint			




Environmental Specifications

Operational Temperature (°C)	-25 to +70
Storage Temperature (°C)	-40 to +105
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.opsi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave, 3 axis both directions


Typical Performance Plots

Loss VS. Ripple VS. Rejection VS.VSWR



Outline Drawing:

All Dimensions in mm [inches]



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.