

Hermetically Sealed Wide Band Power Limiter 1GHz-26GHz



Features

- Passive, High Isolation Limiter
- Low Insertion Loss and Good Return Loss
- High Power Handling Capability up to 10W

Product Description

RFPLT01G26GE-H is a Hermetically Sealed wideband power limiter with a frequency range of 1 to 26GHz.

The max input Power of the limiter is 10W. The typical insertion loss is 2.5 dB and flat Leakage at > 25dBm input is 14dB.

The power limiter's connectors are SMA-female.

The operating temperature of this product is -40 to +85°C.

Typical Applications

- Wireless Infrastructure
- Military and Aerospace Applications
- Test Instrumentation
- Radar Systems
- 5G Wireless Communications
- Microwave Radio Systems
- TR Modules
- Research and Development
- Cellular Base Stations

Electrical Specifications (T_A=+25°C)


Parameter	Min	Typ	Max	Min	Typ	Max	Units
Frequency Range		1 - 4			4 - 26		GHz
CW Input Power		25	27		25	27	dBm
Peak Power Handling (1.0 μs pulse width, 1% duty cycle, ≤15 ns rise time)			45			45	dBm
Insertion Loss		1	1.5		2.5	3.5	dB
VSWR		1.5	2		1.6	2	: 1
Flat Leakage Power		15	17		14	15	dBm
Peak Power Leakage		18	19		16	17	dBm
Weight			0.028 Max.				lbs.
Input / Output Connectors							SMA-Female(Input)-SMA-Male(Output)
Package							Hermetically Sealed (Laser Welded)

Environmental Specifications and Test Standards


Parameter	Description
Operational Temperature	-40°C to +85°C (Case Temperature)
Storage Temperature	-50°C to +105°C
Thermal Shock	-40°C → +85°C (5 Cycles / 10 hours)
**Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Insertion Loss @-40°C



Input VSWR @-40°C




Output VSWR @-40°C




Typical Performance Plots


Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Flat Leakage Power



Peak Power Leakage




Recovery Time




Typical Performance Plots

Limiting Speed




Outline Drawing



Notes:

1. Package Material: Aluminum
2. Plating: Gold
3. All dimensions are in millimeters [inches].
4. Tolerances ± 0.1 [0.004] unless otherwise specified.



Additional Information

Documentation	Webpage
ESD Policy	https://rflambda.com/pdf/rflambda_esd_control.pdf
Connector Torque Specifications	https://www.rflambda.com/pdf/Torque_Specifications.pdf
Random Vibration Test Standard	https://www.rflambda.com/pdf/rflambda_random_vibration_MIL-STD-202G.pdf

Ordering Information

Part Number	Modification	Description
RFPLT01G26GE-H	Input connector SMA-Female and Output connector SMA-Male	1GHz-26GHz Hermetically Sealed Power Limiter

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.