

Mixer (Down-Converting) 40 - 60GHz

Features

- Ultra Wide Band Mixer
- High Dynamic Range

Typical Applications

- Research and Development
- Test and Measurement
- Wireless Infrastructure

Electrical Specifications , $T_A=25\text{ }^\circ\text{C}$


Parameters	Min.	Typ.	Max.	Units
RF Input Frequency	40		60	GHz
IF Output Frequency	DC		1	GHz
LO Power	8		12	dBm
Conversion Gain		-22		dB
Input 1dB Compression Point (P1dB)		-5		dBm
In-Band Spurious rejection		-50		dBc
Harmonic Number		3		
Voltage		+5		V
Current		120		mA
RF / LO/ IF Connectors	WR-19/2.4mm-Female/3.5mm-Female			
Frequency Relationship (N is dividing ratio)	$(RF\pm IF)/N=LO$			

Environmental Specifications and Test Standards

Parameter	Description
Operational Temperature	-20°C~+70°C (Case Temperature)
Storage Temperature	-55°C~+85°C
Thermal Shock	-20°C → +70°C (5 Cycles / 10 hours)
Random Vibration	MIL-STD-202G Table 214-I, Test Condition Letter C 1.5 Hours Per Axis
High Temperature Burn In	Temperature +85°C for 72 Hours
Shock	1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude	Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883 (For Hermetically Sealed Units)

Outline Drawing:

All Dimensions in mm [inches]



Mixer (Down-Converter) 40 - 60GHz



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.