



### Reflective Coaxial SP2T Switch 0.8 - 20GHz



#### Features

- Ultra Wide Band Operation 0.8-20GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation

#### Typical Applications

- Wireless Infrastructure
- Military and Aerospace
- Test and Measurement

Electrical Specifications, TA = +25 °C, Vdd = +5V/-5V, TTL = 0 / +5V

Description	PN: RFSP2TR0020G									
	SP2T Reflective Switch									
	Low Power Cold Switching									
Parameters	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Units
Frequency Range	0.8-8			8-12			12-20			GHz
Insertion Loss		1.5	1.7		1.8	2.2		2.2	2.6	dB
Insertion Loss Temperature Coefficient		0.003			0.003			0.003		dB/°C
Isolation	80	85		80	85		70	82		dB
Input VSWR		1.5	1.8		1.5	1.8		1.5	1.8	:1
Output VSWR		1.5	1.8		1.5	1.8		1.5	1.8	:1
RF Input Power (CW)			30			30			30	dBm
DC Power Dissipation		0.5			0.5			0.5		W
0.1dB Compression Point (Po.1dB)		30			30			30		dBm
IIP3		55			55			55		dBm
Switching Speed	100									ns
Weight	0.71									ounces
Impedance	50									Ω
Bias Current (+5V/-5V)	80/50									mA
Input / Output Connectors	SMA - Female									
Finishing	Gold Plating									
Material	Aluminum									
Sealing	Hermetically Sealed (Optional)									



**Absolute Maximum Ratings**

Biassing	+5V±10%/-5V±10%
TTL Control Voltage	0~0.8V/2.8~5V

**Note:** TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

**Ordering Information**

Part No.	ECCN	Description
RFSP2TR0020G	EAR99	SP2T 0.8-20GHz PIN Diode Switch

**Environmental Specifications and Test Standards**

Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C (Case Temperature)
Storage Temperature		-50°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)




# RF-LAMBDA

## LEADER OF RF BROADBAND SOLUTIONS


# RFSP2TRO020G

### Typical Performance Plots


#### Insertion Loss@+25°C




#### Input VSWR@+25°C




#### Output VSWR@+25°C




#### Isolation@+25°C




#### Insertion Loss@-45°C




#### Input VSWR @-45°C



#### Output VSWR @-45°C




#### Isolation @-45°C




Reflective Coaxial Single Pole Double Throw Switch 0.8-20GHz




**Insertion Loss@+85°C**




**Input VSWR@+85°C**




**Output VSWR@+85°C**




**Isolation@+85°C**



**Switching Speed**




**Switching Speed**





**Outline Drawing:**

All Dimensions in mm [inches]



**Truth Table**

Control Input TTL		State
C1	C2	
0	1	Jo-J1
1	0	Jo-J2
0	0	OFF
1	1	OFF
Control Pin Customization available upon request		



**Important Notice**

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

**Reflective Coaxial Single Pole Double Throw Switch 0.8-20GHz**