




Reflective 6-12GHz Coaxial SP5T Switch



Features

- Wide Band Operation 6-12GHz
- High Power Handle Capability up to 5W upon request.
- TTL compatible driver include
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Temperature Range -45°C~+85°C
- Customization available upon request

Specification	Reflective type					
	PN: RFSP5T R0612G					
	Low		Med		High	
Frequency Range(GHz)	6		9		12	
Insertion Loss(dB)	2.0dB		2.5		3.0dB	
VSWR	1.5		1.8		2.0	
Isolation(dB)	65		65		60	
Switching Speed(ns)	50		50		50	
P1dB Power (dBm)			27			
Absolutely max. Power (W)					5	
Weight (g)	65					
IIP3 (Input IP3) dBm	40					
Impedance(Ohms)	50Ω					
Power Supply (V)	+/-5 V DC					
Current(mA)	200mA (+5V) 100mA (-5V)					
Input Connector	SMA-Female					
Output Connector	SMA-Female					
Finishing	Gold Plating					
Material	Brass					
Seal	Hermetically Sealed					
Control (TTL Driver Included)	TTL Control					
	C5	C4	C3	C2	C1	Status
	1	1	1	1	0	Jo-J1
	1	1	1	0	1	Jo-J2
	1	1	0	1	1	Jo-J3
	1	0	1	1	1	Jo-J4
0	1	1	1	1	Jo-J5	



RF-LAMBDA

The power beyond expectations

RFSP5TR0612G

Reflective Coaxial Single Pole Five Throw Switch 6-12GHz

Absolute Maximum Ratings	
Biasing	+/-5 V
TTL Control Voltage	+5V/0V
Input RF power	+37dBm
Storage Temperature (C°)	-50 ~ +125


Biasing Up Procedure	
Step 1	-5V
Step 2	+5V
Step 3	TTL
Power OFF Procedure	
Step 1	+5V
Step 2	-5V
Step 3	TTL

Environment specifications	
Operational Temperature (C°)	-45 ~ +85
Storage Temperature (C°)	-50 ~ +125
Altitude	30,000 ft (Controlled environment)
Vibration	55g rms (15 degree 2KHz)
Humidity	100% RH at 35c, 95%RH at 40 deg c
Shock	20G for 11msc

Ordering Information		
Part No	ECCN	Description
RFSP5TR0612G	EAR99	SP5T 6-12GHz PIN Diode Switch



Median Lifetime (Tm) vs. Channel Temperature (Tch)






RF-LAMBDA

The power beyond expectations

RFSP5TR0612G



Reflective Coaxial Single Pole Five Throw Switch 6-12GHz

Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.