




Absorptive Coaxial SPST Switch 2 - 8GHz



Features

- Wide Band Operation 2-8GHz
- TTL compatible driver included
- Fast Switching Speed
- Low Insertion Loss and High Isolation
- Customization available upon request

Typical Applications

- Wireless Infrastructure
- Military and Aerospace
- Test and Measurement

Electrical Specifications, TA = +25 °C, Vdd = +5V, Vss = -5V, TTL = 0 / +5V

Description	PN: RFSPSTA0208G			
	SPST Absorptive Switch Jo: Absorptive Port J1: Reflective port			
	Low Power Cold Switching			
Parameters	Min	Typ.	Max	Units
Frequency Range	2-8			GHz
Insertion Loss		0.9	1.2	dB
Insertion Loss Temperature Coefficient		0.003		dB/°C
Isolation (Jo→J1)	80	90		dB
Input VSWR		1.3	1.5	: 1
Output VSWR		1.3	1.5	: 1
RF Input Power (CW)			30	dBm
DC Power Dissipation		0.3		W
0.1dB Compression Point (Po.1dB)		30		dBm
IIP3		55		dBm
Switching Speed		50	100	ns
Weight	0.35			ounces
Impedance	50			Ω
Bias Current(+5V/-5V)	50/50			mA
Input / Output Connectors	SMA - Female			
Finish	Gold Plated			
Material	Aluminum			
Sealing	Hermetically Sealed (optional)			

Absorptive Coaxial Single Pole Single Throw Switch 2 - 8GHz



Absolute Maximum Ratings

Biasing	+5V±10%/-5V±10%
TTL Control Voltage	0~0.8V/2.8~5V

Note: TTL pins cannot be connected to the negative voltage otherwise the internal driver will be damaged.

Ordering Information

Part No.	ECCN	Description
RFSPSTA0208G	EAR99	SPST 2-8GHz PIN Diode Switch

Environmental Specifications and Test Standards


Parameter	Standard	Description
Operational Temperature	MIL-STD-39016	-45°C~+85°C (Case Temperature)
Storage Temperature		-50°C~+125°C
Thermal Shock		1 Hour@ -45°C → 1 Hour @ +85°C (5 Cycles)
Random Vibration		Acceleration Spectral Density 6 (m/s) Total 92.6 RMS
Electrical & Temperature Burn In		Temperature +85°C for 72 Hours
Shock		1. Weight >20g, 50g half sine wave for 11ms, Speed variation 3.44m/s 2. Weight <=20g, 100g Half sine wave for 6ms, Speed variation 3.75m/s 3. Total 18 times (6 directions, 3 repetitions per direction).
Altitude		Standard: 30,000 Ft (Epoxy Sealed Controlled Environment) Optional: Hermetically Sealed (60,000 ft. 1.0 PSI min)
Hermetically Sealed (Optional)	MIL-STD-883	MIL-STD-883 (For Hermetically Sealed Units)

Absorptive Coaxial Single Pole Single Throw Switch 2 - 8GHz




Typical Performance Plots


Insertion Loss @+25°C




Input VSWR @+25°C




Output VSWR @+25°C




Isolation @+25°C




Insertion Loss @-45°C




Input VSWR @-45°C



Output VSWR @-45°C




Isolation @-45°C




Absorptive Coaxial Single Pole Single Throw Switch 2 - 8GHz




Insertion Loss @+85°C




Input VSWR @+85°C




Output VSWR @+85°C




Isolation @+85°C



Switching Speed



Switching Speed




Absorptive Coaxial Single Pole Single Throw Switch 2 - 8GHz



Outline Drawing:

All Dimensions in mm [inches]

[X102]



Truth Table

Control Input TTL	State
1	ON
0	OFF
Control Pin Customization available upon request	



Important Notice

The information contained herein is believed to be reliable. RF-Lambda makes no warranties regarding the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for any of the information contained herein. RF-Lambda assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for RF-Lambda products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. RF-Lambda products are not warranted or authorized for use as critical components in medical, life-saving, or life sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Absorptive Coaxial Single Pole Single Throw Switch 2 - 8GHz