


# FLEXIBLE WAVEGUIDE

--- RFWF187

1.0 Mechanical Specifications	
1.1	Waveguide type Flexible Twistable Waveguide WR187
1.2	Flange type CPRG, CPRF, COVER, CHOKE available
1.3	Flange Holes Through
1.4	Basis-material Aluminum, Brass, Alloyed Cuprum, Stainless
1.5	Outer material Neoprene rubber jacketed
1.6	Internal Body Finish Silver Plated chromate or conversion
1.7	External Body Finish Body painted with gray/black epoxy enamel
1.8	External Body Finish Body painted with gray/black epoxy enamel

2.0 Environment specifications	
2.1	Operation Temp. -54°C--+85°C
2.2	Storage Temp. -60°C--+125°C
2.3	Altitude 40000 ft
2.4	Vibration 12.5g rms (15 degree 2KHz)
2.5	Humidity 100% RH at 35c, 95%RH at 50 deg c
2.6	Shock 20G for 11msc

3.0 Electrical Specifications	
3.1	Frequency Range 3.95-5.85GHz
3.2	Insertion Loss 0.15dB / m
3.3	Power CW / Peak 1000 Watts / 1.5M Watts
3.4	Max. VSWR 1.20:1



MAX RETURN LOSS (dB)			MIN. CENTRELINE BENDING RADII				MAX. TWIST	
			STATIC	STATIC	REPEAT	REPEAT	STATIC	REPEAT
300mm	600mm	1000mm	E-PLANE	H-PLANE	E-PLANE	H-PLANE	deg/m	deg/m
30.2	27.7	27.2	97	197	397	797	145°	51°


**Table 4. FLEXIBLE WAVEGUIDE - STANDARD LENGTHS (mm)**

100	200	300	400	500	600	800	900	1000	1200	1500
A	B	C	D	E	F	G	H	I	J	K
◆	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆

◆ Available unjacketed or with bonded silicone jacket  
○ Available unjacketed or in elastomer sleeving

**Part Number:** **RF W F 187 CF AL S E B**

RF-Lambda  
Waveguide  
Flexible Waveguide  
Waveguide Type Number  
Flange Type: CG=CPRG; CF=CPRF; CO=COVER; CK=CHOKE  
Material: AL=Aluminum; BS=Brass; AC=Alloyed Cuprum; SS=Stainless  
S=STATIC; R=REPEAT  
PLANE TYPE: E=E-PLANE; H=H-PLANE  
Length: A=100mm; B=200m (Refer Table 4)

PAGE 1 OF 1	DATE Apr 1 <sup>st</sup> 2008
PROPRIETARY INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF RF-LAMBDA EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITINGS BY RF-LAMBDA. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN THE WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION OF ALL THIRD PARTIES AND SHALL USE SAME FOR OPERATING AND MAINTENANCE PURPOSES ONLY	DESIGN RFPC
 <b>RFWF187 FLEXIBLE WAVEGUIDE</b>	RF-LAMBDA RFPC
www.rflambda.com	CAD MODEL REVISION 065-23
RF-LAMBDA	ASSEMBLY REVISION VS1124
SIZE LT	ASSEMBLY NAME RFLVRO2K
SHEETS 1 OF 1	DRAWING NUMBER D056-2